

3MP IP CAMERA

OD-VPI326-32 P



- ❖ سنسور تصویر 3 مگا پیکسل (2048*1536) CMOS SONY SENSOR
- ❖ لنز با قابلیت CS mount
- ❖ فشرده سازی با فرمت H264 ,H265 ,MJPEG
- ❖ قابلیت ارسال دو Stream به صورت مجزا
- ❖ گستره دینامیکی True WDR(120 db)
- ❖ پشتیبانی از پروتکل های : IPV4 ، UDP ، TCP ، HTTP ، DHCP ، DDNS
- ❖ قابلیت POE
- ❖ قابلیت ارتباطی ONVIF

OD-VPI326-32 P

▶ Camera

Image Sensor	Type: 1/2.8 inch Sony Progressive Scan CMOS Pixels: 2048*1536 (2MP)
FPS	FPS by user (1-30)
LENS	CS mount, , IR, I-CS Technology
Shutter	Fixed (1/25s to 1/10000s) /Auto
Resolutions (H× V)	2048*1536
White balance	Auto ,Manual , Selectable
3D Noise reduction	Yes
Dynamic Range	True WDR 120db
Bandwidth Management	Variable & certain Bit rate
DAY/NIGHT	True D/N/ Auto(IRC), Manual
Minimum Illumination (color)	0.05 Lux without IR
Minimum Illumination (B/W)	0.01 Lux with IR LED

▶ Audio (optional)

AUDIO	Linear Audio Input /Output Interface
AUDIO IN	Yes (option)
AUDIO Out	Yes (option)
Standard	G.711A , G.726 , G.711U

▶ System Integration

Alarm Input	Yes
Alarm Out	Yes

▶ video

VIDEO COMPRESSION H.264B/H.264H/H.264M/MJPG/H.265

Main stream: Multicast off
1920*1080@30fps/1280*720@30FPS

STREAMING

Sub stream : Multicast off
704*576@30fps/640*480@30fps/640*352@30fps/320*240@30fps

3main Stream + 3 sub Stream:
Multicast on

Watermark Yes

▶ Network

SECURITY

Password protection, user access privilege ; Server platform

Unit configuration

Via web browser or configuration manager

Connectivity

ONVIF

Ethernet

10/100 Base-T, Auto negotiating

Ethernet connector

RJ45 10M/100M Self, Auto negotiating

Protocol

IPV4,UDP,TCP,HTTP,DHCP,DDNS, DNS,UPNP,PPOE,RTSP,FTP, NTP,IGMP,ICMP

▶ Smart

Smart Detect Focus	Yes
Motion Alarm	Yes
Smart Cover Detect	Yes
Motion Record	Yes
Intelligent video analytic	Line crossing , region invitation (optional)

OD-VPI326-32 P

Maintenance

Software update	Web Browser , Remotely
-----------------	------------------------

Recording

Recording on	FTP Server , SD CARD , RTSP, local on pc
Recording mode	continuous, trigger, motion
Memory card slot (optional)	Micro SD cards support up to 128 GB

General

Power consumption	12v-DC
Power	10W
POE	High POE, IEEE 802.3AT
Sensitivity	3200 K , 35 %IRE
IR	Input trigger
Ingress Protection	IP66
MTBF	84000 Hours calculated by Component Specification
Operating temperature	-10°C to +75°C
Storage temperature NVR	-15°C to +80°C 80,000
Operating humidity	Up to 95%
Approval	Sharif University of Technology, EMP, EMC

Case

Material	Aluminum
Color	White
Vandal Proof Parameter	IK10

Connection (Interface)

Ethernet Port	Yes
Power in	Yes
Reset Bottom	Yes