

IP DOME CAMERA



OD-VPI551MLPVS



- ❖ سنسور تصویر 5 مگا پیکسل (2560*1920) - CMOS SONY SENSOR
- ❖ لنز موتورایز Varifocal 2.8-12 mm
- ❖ قابلیت فشرده سازی با فرمت H264, H265, MJPG به صورت همزمان
- ❖ قابلیت ارسال دو Stream بصورت همزمان
- ❖ قابلیت تشخیص حرکت
- ❖ قابلیت WDR(120dB)
- ❖ قابلیت دید در شب
- ❖ پشتیبانی از پروتکل های : IPV4 ، UDP ، TCP ، HTTP ، DHCP ، DDNS
- ❖ قابلیت POE
- ❖ قابلیت ارتباطی ONVIF

OD-VPI551MLPVS

OD-VPI551MLPVS

▶ Camera

IMAGE sensor	Type: 1/2.8 inch Sony Progressive Scan CMOS Pixels: 5MP
FPS	25/30 FPS Adjustable by user (1-25)/(1-30)
LENS (F.Stop<1.4)	2.8-12 mm Vari-Focal, Mega Pixel
Adjustment	Motorized zoom, Auto Focus
Iris Control	Auto control
SHUTTER	Fixed (1/25s to 1/10000s) and Auto Shutter
Resolutions (H× V)	2560*1920
White balance	Auto ,Manual , Selectable
Noise reduction	3D support
Sense	Selectable for different condition
Dynamic Range	Up to 120dB
Bandwidth Management	Yes (VBR & CBR Bandwidth control)
Privacy Masking	Four independent areas
DAY/NIGHT(True D/N)	Auto(IRC) , Timing , Manual , Alarm Trigger
Minimum Illumination (color)	0.1 Lux without IR
Minimum Illumination (B/W)	0 Lux with IR LED

▶ System Integration (optional)

I/O In	Yes
I/O Out	Yes
Alarm Input	Yes
Alarm Out	Yes

▶ video

VIDEO COMPRESSION	H.264B/H.264H/H.264M/MJPG/H.265
STREAMING	Main stream: With Multicast off 2048*1536@30fps/1920*1080@30fps/1280*720@30fps Sub stream :With Multicast off 704*576@30fps/640*480@30fps/640*352@30fps/320*240@30fps 3main Stream + 3 sub Stream: with Multicast on
Watermark	Yes

▶ Network

SECURITY	Password protection, user access privilege ; Server platform
Unit configuration	Via web browser or configuration manager
Connectivity	ONVIF
Ethernet	10/100 Base-T, Auto negotiating
Ethernet connector	RJ45 10M/100M Self-Adaption Ethernet Port POE
Protocol	IPV4,UDP,TCP,HTTP,DHCP,DDNS, DNS,UPNP,PPOE,RTSP,FTP,P2P, NTP,IGMP,ICMP

▶ Audio (optional)

AUDIO	Linear Audio Input /Output Interface
AUDIO IN	Yes
AUDIO Out	Yes
Standard	G.711A , G.726 , G.711U

OD-VPI551MLPVS

▶ Smart

Smart Detect Focus	Yes
Motion Alarm	Yes
Smart Cover Detect	Yes
Motion Record	Yes

▶ Maintenance

Software update	Web Browser , Remotly
-----------------	-----------------------

▶ General

Power consumption	12v-DC
POE	IEEE 802.3AF
Sensitivity	3200 K , 35 %IRE
IR	30m
Water / dust protection	IP66 / water & dust resistance
MTBF	84000 Hours calculated by Component Specification
Operating temperature	-20°C to +70°C
Storage temperature	-30°C to +70°C
Operating humidity	Up to 95%
Guaranty time	2years

▶ Recording

Continuous Recording FTP Server , SD CARD , TCP/UDP/RTSP

Memory card slot(optional) Micro SD cards up to 128 GB

▶ Case

Material	Aluminum
Color	White
Fan Support	Yes
Brackets	Cable Management

▶ Connection (Interface)

Ethernet Port	Yes
Power in	Yes
Reset Bottom	Yes