

Stand Alone 36 CH NVR

OD-LP4216-3336



❖ پشتیبانی از دو استریم به صورت همزمان

❖ سیستم عامل OS Linux

❖ قابلیت ریموت مانیتورینگ و ۱۶ کانال play back به صورت همزمان

❖ دارای خروجی آلام و صدا

❖ قابلیت تنظیم مشخصه های عمومی دوربین به صورت همزمان

❖ قابلیت گروه بندی هارد دیسک بر اساس کانال های تصویری

❖ قابلیت مانیتورینگ هوشمند شبکه، ترافیک شبکه، packetloss

❖ پشتیبانی از Raid ، 0 ، 1 ، 5 ، 6 ، 10

❖ پشتیبانی از Nas, IPSAN



OD-LP4216-3336

Operation System	Embedded Linux
Display Rate (NTSC/PAL)	30 FPS For Each Channel Up to 4K (3840*2160)
Video Input	20 ch video 36 ch video 64 ch video
Recording Rate (NTSC/PAL)	30 FPS(NTSC), 25 FPS(PAL) For each channel simultaneous
Motion Detection	Each channel can set detection areas and set 6-level sensitivity
Recording Mode	Support manual , auto, alarm trigger record mode
Playback	4 Channel 3MP 25 FPS Simultaneously
Region Cover	Every channel can set 4 cover regions
Backup	Support U disk, USB mobile HDD, network storage and backup, Cloud Storage
I/O (option)	8 Channel Alarm Input , 1 Channel Alarm Output
Audio Compression	G.711

VIDEO OUTPUT	1VGA and 1HDMI
USB Interface	3 USB port
HDD SUPPORT	4*10TB Totally 40TB
Communication Interface	2 RJ45,10M/100M/1000M, 4 port Controller , Auto negotiate RS485
Dual Steam	Supported
Power Supply	AC220V -50 Hz , Dual Power Supply (optional) 7*24
Power Consumption	≤30W (without HDD)
Working Temperature	-10° C ~ +55° C
Working Humidity	10%-90%
Atmosphere Pressure	86kpa~106kpa
Casing	2Unit Rack mount
Surveillance Software	CMS Software
Operation System	Embedded Linux
User Level	Administrator User Guest
MTBF	80000 Hours calculated by Component Specification
Remote Configuration	Yes
Total Recording Bitrate (bandwidth)	UP to 640Mb
Monitoring	Web viewer , CMS , RTSP