

**IP DOME CAMERA**

**OD-VPI325-31MLPVS**



- ❖ سنسور تصویر **3** مگا پیکسل ( 2048\*1536 ) - CMOS SONY SENSOR
- ❖ لنز موتورایز Varifocal 2.8-12 mm
- ❖ قابلیت فشرده سازی با فرمت H264,H265,MJPG به صورت همزمان
- ❖ قابلیت ارسال دو Stream بصورت همزمان
- ❖ قابلیت تشخیص حرکت
- ❖ قابلیت WDR(120dB)
- ❖ قابلیت دید در شب
- ❖ پشتیبانی از پروتکل های : IPV4 ، UDP ، TCP ، HTTP ، DHCP ، DDNS
- ❖ قابلیت POE
- ❖ قابلیت ارتباطی ONVIF

## OD-VPI325-31MLPVS

### ▶ Camera

<b>IMAGE sensor</b>	Type: 1/2.8 inch Sony Progressive Scan CMOS Pixels: 2048*1536 ( 3MP)
<b>FPS</b>	25/30 FPS Adjustable by user ( 1-25)/(1-30)
<b>LENS (F.Stop&lt;1.4)</b>	2.8-12 mm Vari-Focal, Mega Pixel
<b>Adjustment</b>	Motorized zoom, Auto Focus
<b>Iris Control</b>	Auto control
<b>SHUTTER</b>	Fixed ( 1/25s to 1/10000s ) and Auto Shutter
<b>Resolutions ( H× V )</b>	2048*1536
<b>White balance</b>	Auto ,Manual , Selectable
<b>Noise reduction</b>	3D support
<b>Sense</b>	Selectable for different condition
<b>Dynamic Range</b>	Up to 120dB
<b>Bandwidth Management</b>	Yes (VBR & CBR Bandwidth control)
<b>Privacy Masking</b>	Four independent areas
<b>DAY/NIGHT(True D/N)</b>	Auto(IRC) , Timing , Manual , Alarm Trigger
<b>Minimum Illumination (color)</b>	0.1 Lux without IR
<b>Minimum Illumination (B/W)</b>	0 Lux with IR LED

### ▶ System Integration (optional)

<b>I/O In</b>	Yes
<b>I/O Out</b>	Yes
<b>Alarm Input</b>	Yes
<b>Alarm Out</b>	Yes

### ▶ video

**VIDEO COMPRESSION** H.264B/H.264H/H.264M/MJPG/H.265

<b>STREAMING</b>	Main stream: With Multicast off 2048*1536@30fps/1920*1080@30fps/1280*720@30fps Sub stream :With Multicast off 704*576@30fps/640*480@30fps/640*352@30fps/320*240@30fps 3main Stream + 3 sub Stream: with Multicast on
<b>Watermark</b>	Yes

### ▶ Network

<b>SECURITY</b>	Password protection, user access privilege ; Server platform
<b>Unit configuration</b>	Via web browser or configuration manager
<b>Connectivity</b>	ONVIF
<b>Ethernet</b>	10/100 Base-T, Auto negotiating
<b>Ethernet connector</b>	RJ45 10M/100M Self-Adaption Ethernet Port POE
<b>Protocol</b>	IPV4,UDP,TCP,HTTP,DHCP,DDNS, DNS,UPNP,PPOE,RTSP,FTP,P2P, NTP,IGMP,ICMP

### ▶ Audio (optional)

<b>AUDIO</b>	Linear Audio Input /Output Interface
<b>AUDIO IN</b>	Yes
<b>AUDIO Out</b>	Yes
<b>Standard</b>	G.711A , G.726 , G.711U

## OD-VPI325-31MLPVS

### ▶ Smart

Smart Detect Focus	Yes
Motion Alarm	Yes
Smart Cover Detect	Yes
Motion Record	Yes

### ▶ Maintenance

Software update	Web Browser , Remotly
-----------------	-----------------------

### ▶ General

Power consumption	12v-DC
POE	IEEE 802.3AF
Sensitivity	3200 K , 35 %IRE
IR	30m
Water / dust protection	IP66 / water & dust resistance
MTBF	84000 Hours calculated by Component Specification
Operating temperature	-20°C to +70°C
Storage temperature	-30°C to +70°C
Operating humidity	Up to 95%
Guaranty time	2years

### ▶ Recording

Continuous Recording FTP Server , SD CARD , TCP/UDP/RTSP

Memory card slot(optional) Micro SD cards up to 128 GB

### ▶ Case

Material	Aluminum
Color	White
Fan Support	Yes
Brackets	Cable Management

### ▶ Connection (Interface)

Ethernet Port	Yes
Power in	Yes
Reset Bottom	Yes