

2MP IP SPEED DOME CAMERA

OD-EPI720



❖ سنسور تصویر CMOS 2 Mega pixel effective pixel

❖ High speed Auto focus lens (4.8-173mm)

❖ حداقل روشنایی 0.05lux

❖ H.264 and MJPEG & H.265

❖ زوم اپتیکال 36X

❖ IRWDR (UP TO 80db)

❖ AWB

❖ دارای IR تا فاصله ۱۵۰ متر (adaptive)

❖ با قابلیت Wiper

❖ کلاس عایقی IP66 HOUSING

2MP IP SPEED DOME CAMERA

▶ Camera

Image Sensor	1/2.8" CMOS 2 MP CMOS
Minimum Illumination	0.01 Lux
Dynamic Range	UP TO 120 db
S/N RATIO	More than 48dB
Shutter Speed	1/2 s to 1/10,000s, 21 steps
Sync System	Internal Synchronization
White Balance	Auto, ATW, Indoor, Outdoor
Zoom Ratio	Optical Zoom 36x
Focal Length	4.8 ~ 173mm
PAN/TILT Angle	360° endless rotation, 180° Auto rotate
Preset Position	255
Number of Effective Pixels (HxV)	1920x1080 (HxV)

▶ Camera features

DAY/NIGHT	YES and ICR
Noise Reduction	Yes
Image Stabilizer	Yes
Video Buffer	24MB Max

▶ Image

Video Compression Format	H.264, MJPEG, H.265
Codec Streaming Capability	Dual Streaming
Maximum Frame Rate	264.: Up to 30FPS (1920*1080) 265.: Up to 30FPS (1920*1080)

▶ Network

Protocol	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, FTP, SNMP
ONVIF Conformance	Yes
WEB BROWSER	Internet Explorer 8 or above, Chrome, Firefox

▶ Interface

Network Port	10Base-T/100Base-TX (RJ-45)
Sensor Input	1 Input/ 1Output
Alarm Output	1, 24V AC/DC, 3A (mechanical relay outputs electrically isolated from the camera)
Microphone Input	EX Connector

▶ General

Power Requirements	AC 24V, 3 A
Security	User Account and Password Protection
Fan and Heater	Yes
MTBF	84000 Hours calculated by Component Specification
IK Grade	IK10
operating Temperature	-30 °C ~ 70 °C
Operating Humidity	20% to 80%

Ingress Protection	IP66
--------------------	------

▶ Audio

Audio Compression Format	G.711 & G.726
--------------------------	---------------